



TORAY INDUSTRIES INC
NIHONBASHI-MITSUI TOWER
1-1 NIHONBASHI-MUROMACHI 2-CHOME
CHUO-KU, TOKYO 103-8666 Japan



Toyolac: 920 555 U

Methyl Methacrylate Acrylonitrile Butadiene Styrene (MABS), pellets

可燃性	值	测试方法
UL 阻燃等级		
1.2 mm, ALL	HB	UL 94
1.5 mm, ALL	HB	UL 94
2.5 mm, ALL	HB	UL 94
3.0 mm, ALL	HB	UL 94
3.0 mm, ALL	HB40	IEC 60695-11-10, -20
1.2 mm, ALL	HB75	IEC 60695-11-10, -20
1.5 mm, ALL	HB75	IEC 60695-11-10, -20
2.5 mm, ALL	HB75	IEC 60695-11-10, -20
电气性能	值	测试方法
热丝引燃 (HWI)		UL 746A
2.5 mm	PLC 4	
3.0 mm	PLC 4	
高电弧燃烧指数(HAI)		UL 746A
1.5 mm	PLC 0	
2.5 mm	PLC 0	
3.0 mm	PLC 0	
热性能	值	测试方法
RTI Elec		UL 746B
1.2 mm	50.0 °C	
1.5 mm	50.0 °C	
2.5 mm	50.0 °C	
3.0 mm	50.0 °C	
RTI Imp		UL 746B
1.2 mm	50.0 °C	
1.5 mm	50.0 °C	
2.5 mm	50.0 °C	
3.0 mm	50.0 °C	
RTI		UL 746B
1.2 mm	50.0 °C	
1.5 mm	50.0 °C	
2.5 mm	50.0 °C	
3.0 mm	50.0 °C	