

General Information

TAFMER™ MA9015, acid modified polyolefin, is used as a modifier to improve adhesive strength of Polyethylene (PE) to Aluminum.

Physical Attributes:	Low specific gravity High flowability
Chemical Attributes:	Chemically stable Low hygroscopic
EU Directive Conformity:	Conforms to EU Directive Please contact Mitsui sales representatives for more information
Others:	Packed in pellet form Gel content controlled

Physical Properties	Test Method	Unit	Value
MFR(190°C/2.16kg)	ASTM D1238	g/10min	11
MFR(230°C/2.16kg)	ASTM D1238	g/10min	23
Density	ASTM D1505	kg/m ³	896
Mechanical Properties	Test Method	Unit	Value
Tensile Strength at Break	ASTM D638	MPa	16
Elongation at Break	ASTM D638	%	850
Surface Hardness (Shore A)	ASTM D2240	—	89
Thermal Properties	Test Method	Unit	Value
Brittleness Temperature	ASTM D746	°C	< -70

Disclaimer:

Information contained herein is based on the material, information and data available as of the end of December 2011. No warranty is given for any data or evaluation results contained herein. It is also assumed that the product is to be used under normal conditions and with due precautions. If the product is to be used in any special manner, the user is requested safety measures to meet such new use or application.