

General Information

TAFMER™ PN-2070, propylene based polymer, is a specialty olefinic resin designed to improve transparency, flexibility, softness and impact resistance of Polypropylene (PP).

Physical Attributes:

- Low specific gravity
- High melting point
- Softness and elasticity
- Excellent transparency due to nano-size controlled crystals
- Good impact resistance
- Anti-stress whitening

Chemical Attributes: PP miscibility

FDA/EU Directive Conformity: Conforms to FDA and EU Directive
 Please contact Mitsui sales representatives for more information

Others:

- Packed in pellet form
- Gel content controlled

Physical Properties	Test Method	UNIT	Value
MFR(230°C)	ASTM D1238	g/10min	7.0
Transmittance	MCI Method in Cyclohexanol	%	98
Mechanical Properties	Test Method	Unit	Value
Yielding Strength	ASTM D638	MPa	-
Tensile Strength at Break	ASTM D638	MPa	> 14
Elongation at Break	ASTM D638	%	> 1000
Young's Modulus	ASTM D638	MPa	14
Surface Hardness (Shore A)	ASTM D2240	—	75
Thermal Properties	Test Method	Unit	Value
Melting Point	MCI Method	°C	140
Brittleness Temperature	ASTM D746	°C	-28

Disclaimer:

Information contained herein is based on the material, information and data available as of the end of December 2011. No warranty is given for any data or evaluation results contained herein. It is also assumed that the product is to be used under normal conditions and with due precautions. If the product is to be used in any special manner, the user is requested safety measures to meet such new use or application.