

# KEPITAL® TE-22

toughened, medium-viscosity grade

KEPITAL® TE-22 is a toughened, medium-viscosity grade for general injection molding. Suitable for applications requiring high impact resistance, reduced impact noise, and quality surface.

## Rheological properties

Moulding shrinkage, parallel	1.7 %	ISO 294-4, 2577
------------------------------	-------	-----------------

## Typical mechanical properties

Yield stress, 50mm/min	51 MPa	ISO 527-1/-2
Yield strain, 50mm/min	11 %	ISO 527-1/-2
Nominal strain at break	>50 %	ISO 527-1/-2
Flexural Modulus	1900 MPa	ISO 178
Flexural Strength	68 MPa	ISO 178
Charpy notched impact strength, 23°C	11 kJ/m <sup>2</sup>	ISO 179/1eA

## Thermal properties

Melting temperature, 10°C/min	165 °C	ISO 11357-1/-3
Temp. of deflection under load, 1.8 MPa	76 °C	ISO 75-1/-2
Coeff. of linear therm. expansion, parallel	130 E-6/K	ISO 11359-1/-2

## Other properties

Humidity absorption, 2mm	0.23 %	Sim. to ISO 62
Density	1370 kg/m <sup>3</sup>	ISO 1183