Technical Information

TI/EVK 1053 e September 2010

Page 1 of 2

Plastic Additives



® = registered trademark of BASF SE

Irgastab[®] PVC 11 EM

New liquid stabilizer emulsion for PVC polymerization processes

Characterization

Irgastab PVC 11 EM is a 40% active aqueous micro-emulsion of Irgastab PVC 11, a thermal stabilizer package for vinyl polymers. It protects the substrates against thermal degradation of polyvinyl chloride (PVC) during manufacturing, processing and end-use.

Applications

Irgastab PVC 11 EM is recommended particularly for the stabilization of PVC. In addition to imparting thermal stability to the finished polymer, Irgastab PVC 11 EM is effective as chain stopper during PVC polymerization.

Features/benefits

The desired quantity of Irgastab PVC 11 EM can easily be added or dosed into the polymerization system. Because the thermal stabilizer is uniformly dispersed in the reaction mixture, the resulting PVC develops improved qualities, such as excellent heat stability, low color and high thermal stability. The formation of fish eyes in film applications can also be reduced considerably. Additionally, Irgastab PVC 11 EM imparts excellent chain terminating properties during PVC polymerization.

Product forms

Irgastab PVC 11 EM white to slightly yellow liquid emulsion

Guidelines for use

Irgastab PVC 11 EM can be recommended at concentration levels of about 0.03% - 0.08% as chain stopper for the PVC polymerization.

Physical properties

Particle size distribution $1-10 \mu m$ Specific gravity (25 °C) 0.97 g/mlViscosity (25 °C, shear rate $\geq 58 \text{ s}^{-1}$) $\leq 300 \text{ mPa} \cdot \text{s}$ Vapor pressure (20 °C) 4 E-6 Pa

Health & Safety

Irgastab PVC 11 EM exhibits a very low order of oral toxicity and does not present any abnormal problems in its handling or general use.

Detailed information on handling and any precautions to be observed in the use of the product(s) described in this leaflet can be found in our relevant health and safety information sheet.

Note

The descriptions, designs, data and information contained herein are presented in good faith, and are based on BASF's current knowledge and experience. They are provided for guidance only, and do not constitute the agreed contractual quality of the product or a part of BASF's terms and conditions of sale. Because many factors may affect processing or application/use of the product, BASF recommends that the reader carry out its own investigations and tests to determine the suitability of a product for its particular purpose prior to use. It is the responsibility of the recipient of product to ensure that any proprietary rights and existing laws and legislation are observed. No warranties of any kind, either expressed or implied, including, but not limited to, warranties of merchantability or fitness for a particular purpose, are made regarding products described or designs, data or information set forth herein, or that the products, descriptions, designs, data or information may be used without infringing the intellectual property rights of others. Any descriptions, designs, data and information given in this publication may change without prior information. The descriptions, designs, data and information furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for the descriptions, designs, data or information given or results obtained, all such being given and accepted at the reader's risk.

September 2010