# **Technical Data Sheet**

# Pro-fax SR549M



Polypropylene, Random Copolymer

## **Product Description**

*Pro-fax* SR549M clarified polypropylene random copolymer is available in pellet form. This resin is typically used in injection molding and injection-stretch blow molding applications and offers good see-through and contact clarity.

## **Regulatory Status**

For regulatory compliance information, see *Pro-fax* SR549M <u>Product Stewardship Bulletin (PSB) and Safety</u> Data Sheet (SDS).

Status Commercial: Active
Availability North America

Application Caps & Closures; Clear Containers

Market Consumer Products; Rigid Packaging

Processing Method Injection Molding; Injection Stretch Blow Molding

Attribute Contains Antistat; Good Impact Resistance; High Clarity

Nominal Value	English Units	Nominal Value	SI Units	Test Method
,			<u> </u>	
11	g/10 min	11	g/10 min	ASTM D1238
0.90	g/cm³	0.90	g/cm³	ASTM D792
150000	psi			ASTM D790
		1030	MPa	ASTM D790
4300	psi			ASTM D638
		30	MPa	ASTM D638
12	%	12	%	ASTM D638
1.2	ft-lb/in			ASTM D256
		64	J/m	ASTM D256
170	°F			ASTM D648
		77	°C	ASTM D648
7	%	7	%	ASTM D1003
	11 0.90 150000 4300 12 1.2	Value         Units           11         g/10 min           0.90         g/cm³           150000         psi           4300         psi           12         %           1.2         ft-lb/in           170         °F	Value         Units         Value           11         g/10 min         11           0.90         g/cm³         0.90           150000         psi         1030           4300         psi         30           12         %         12           1.2         ft-lb/in         64           170         °F         77	Value         Units         Value         Units           11         g/10 min         11         g/10 min           0.90         g/cm³         0.90         g/cm³           150000         psi         1030         MPa           4300         psi         30         MPa           12         %         12         %           1.2         ft-lb/in         64         J/m

### **Notes**

These are typical property values not to be construed as specification limits.

## **Processing Techniques**

Specific recommendations for resin type and processing conditions can only be made when the end use, required properties and fabrication equipment are known.

### **Company Information**

For further information regarding the LyondellBasell company, please visit <a href="http://www.lyb.com/">http://www.lyb.com/</a>.

© LyondellBasell Industries Holdings, B.V. 2018

#### Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative.

#### **Trademarks**

The Trademark referenced within the product name is owned or used by the LyondellBasell family of companies.

LyondellBasell Technical Data Sheet Date: 12/4/2023