



Component - Plastics

File Number: E162823

FORMOSA CHEMICALS & FIBRE CORP PLASTICS DIV

201 TUNG HWA N RD

TAIPEI, 105 Taiwan



TAIRILOY: AC325(+)

Polycarbonate/Acrylonitrile Butadiene Styrene (PC/ABS), pellets, mineral reinforced

(+) - Replace by one digital 0-9 or one alphabet A-Z, unconcerned with formula or constituent changed

Flammability	Value	Test Method
Flame Rating		UL 94
1.2 mm, ALL	V-0	IEC 60695-11-10, -20
2.0 mm, ALL	V-0, 5VB	
3.0 mm, ALL	V-0, 5VA	
Electrical	Value	Test Method
Hot-wire Ignition (HWI)		UL 746
1.2 mm	PLC 2	
2.0 mm	PLC 2	
3.0 mm	PLC 0	
High Amp Arc Ignition (HAI)		UL 746
1.2 mm	PLC 4	
2.0 mm	PLC 4	
3.0 mm	PLC 4	
Comparative Tracking Index (CTI)	PLC 3	UL 746
High Voltage Arc Tracking Rate (HVTR)	PLC 3	UL 746
Arc Resistance	PLC 7	ASTM D495
Thermal	Value	Test Method
RTI Elec		UL 746B
1.2 mm	90.0 °C	
2.0 mm	90.0 °C	
3.0 mm	90.0 °C	
RTI Imp		UL 746B
1.2 mm	85.0 °C	
2.0 mm	85.0 °C	
3.0 mm	85.0 °C	
RTI Str		UL 746B
1.2 mm	90.0 °C	
2.0 mm	90.0 °C	
3.0 mm	90.0 °C	